



Technical data sheet in accordance with ASTM

Material FKM FP603401

brown

cross linking: bisphenolically

revision index 2	revision date 7/3/2017		p	age 1/2
Physical properties		nominal range	typical values	
Density ASTM D 1817, 23 °C		1.98 ±0.02	1.98	g/cm³
Hardness ASTM D2240, Shore A, 23 °C		60 ±5	60	Shore
Tensile strength ASTM D412			12.1	MPa
Elongation at Break ASTM D412			261	%
Tear strength ASTM D624, C, 23 °C			33	KN/m
Compression set ASTM D395, B, 22 h, 200 °C,	25 %		12	%
Low temperature test ASTM D1329, TR10			-16	°C
Declarations of conformity				
Co RoHS conform	untry Part	Remark including EU 2011/65 and EU2015/863 (ROHS III)	Expires	unlimited ✓
Change after aging in Air: 70h/250°C			Typ. values Base value After aging difference	
Hardness (ASTM D2240, Shore A, 2 Tensile strength (ASTM D412) Elongation at Break (ASTM D412) volume change (ASTM D471)	3 °C)	Shore MPa %		62 2 14.3 18 % 68.8 3 % -2

Freudenberg

Freudenberg Industrial Services GmbH Global Material Technology Nadja Güldner Telefon: +49 6201 80 2182 Fax: -Email: nadja.gueldner@fst.com





Technical data sheet in accordance with ASTM

Material FKM FP603401

cross linking: bisphenolically

revision index

revision date 7/3/2017

page 2/2

No ASTM D2000 properties available

The given values are based on a limited number of tests on standard test pieces (2mm sheets). The data from finished parts can deviate from above values depending on the manufactories process and the component geometry.

The data represents our present empirical values. It is incumbent on the person placing the order to examine whether it is suitable for its intended purpose, before using the product. All questions regarding the guarantee of this product are in line with our terms and conditions, inasmuch as statutory provisons do not plan for something else.

Freudenberg

Freudenberg Industrial Services GmbH Global Material Technology Nadja Güldner Telefon: +49 6201 80 2182 Fax: -Email: nadja.gueldner@fst.com